



Industrial 2.5" form-factor 40/44-pin IDE to CF card adapter



Common Specifications:

❖ Form-factor	2.5" form-factor with 4 standard 2.5" HDD Fixed holes
❖ Interface	40-pin (2.54mm pixel) male IDE connector *1 44-pin (2.00mm pixel) male IDE connector *1
❖ CF Socket	CompactFlash type II socket with ejector
❖ Power Connector	40-pin IDE adapter equipped with a 4-pin floppy power connector
❖ Master / Slave Setup	By jumper
❖ Support Card Types	CompactFlash card type I/II and MicroDrive
❖ Data Transfer Mode	Support PIO mode, DMA mode and up to UDMA-4 mode
❖ LED Indicator	Optional for special request
❖ Bootable	Yes
❖ Hot Swappable	No
❖ Operation Voltage	+5V
❖ Supported OS	Compatible with DOS, Windows 3.1/ NT4/ 98SE/ME/ 2000/XP and Linux
❖ Dimension	75 mm * 70 mm
❖ Weight	40 g / 1.41oz
❖ Warranty	1 year warranty
❖ RoHS compliant	Yes

Part Number List

AD-CF125IDE04003R	Host side IDE 40 + 44-pin male connector to CF type II socket * 1
AD-CF125IDE0X003R	Host side IDE 40-pin male connector to CF type II socket * 1
AD-CF125IDEX4003R	Host side IDE 44-pin male connector to CF type II socket * 1

INDUSTRIAL
CompactFlash Card

INDUSTRIAL
PCMCIA ATA Card

INDUSTRIAL
micro IDE Flash Disk

INDUSTRIAL
micro SATA Flash Disk

INDUSTRIAL
Solid State Disk

INDUSTRIAL
USB Flash Disk

INDUSTRIAL
Adapter Card Reader