



WD SiliconDrive® A100

2.5-inch Solid State Drives

Embedded SSD performance and reliability.

These fast performing drives offer low power consumption along with best-in-class reliability. WD SiliconDrive A100 drives are built with the quality and reliability WD drives are known for worldwide and carry a 5-year limited warranty.



Product Highlights

- Fast sequential data transfer
- Best-in-class reliability
- High tolerance to shock and vibration
- Low power consumption

Product Features

Advanced wear-leveling

Lengthens drive life and preserves drive speed with a combination of dynamic and static wear-leveling algorithms designed to overcome performance degradation issues occurring in traditional SSDs that result from continual heavy use.

ATA SMART commands

Self-Monitoring Analysis and Reporting Technologies (SMART) detect and warn when the drive needs replacement.

Advanced error correction

Enables error free data transmission by deploying advanced error correction technologies to detect and correct errors resulting from signal noise or other kinds of interference that cause data distortion.

Security

Runs ATA-8 security feature sets and Secure Erase to protect sensitive data.

Data integrity protection

Protects against bit flips and data corruption from read disturb issues intrinsic to NAND media.

Markets

- Industrial automation
- Interactive kiosks
- Medical
- Military
- Netcom
- Telecom and networking infrastructure
- Transportation
- Video surveillance

Applications

- Data base or multimedia servers
- Digital graphics rendering
- POS terminals
- Video on demand
- Wireless infrastructure

PUT YOUR LIFE ON IT®



WD SiliconDrive A100

Specifications ¹	WD SiliconDrive A100				
Model number ²	SSD-D0008S(x)-7100	SSD-D0016S(x)-7100	SSD-D0032S(x)-7100	SSD-D0064S(x)-7100	SSD-D0128S(x)-7100
Formatted capacity	8 GB	16 GB	32 GB	64 GB	128 GB
User sectors per drive	15,625,008	31,250,016	62,500,032	125,000,064	250,069,680
Form factor	2.5-inch				
Interface	SATA 3 Gb/s				
Interface connector	SATA				
Hot swappable	Yes				
RoHS compliant ³	RoHS 6/6				
Performance					
Interface burst speed	3 Gb/s				
Maximum read transfer rate ⁴	Up to 120 MB/s	Up to 120 MB/s	Up to 120 MB/s	Up to 120 MB/s	Up to 230 MB/s
Maximum write transfer rate ⁴	Up to 100 MB/s	Up to 100 MB/s	Up to 110 MB/s	Up to 110 MB/s	Up to 190 MB/s
Reliability/Data Integrity					
MTBF (hours)	1,500,000				
Non-recoverable read errors per bits read	<1 in 10 ¹⁵				
Limited warranty ⁵	5 years				
Operational Lifespan - LifeEST™					
Read	Unlimited				
Service Life	10 years				
Maximum TB written (TBW) ⁶	40	80	160	320	640
Power Management					
DC input voltage	5V				
Idle (average watts)	0.4W				
Active (average watts)	1.0W				
Environmental					
Operating temperature (°C) Standard temperature (C) ² Extended temperature (I) ²	0 to 70 -40 to 85				
Non-operating temperature	-55 to 125				
Relative humidity (non-condensing)	8% to 95%				
Operating Shock	1000G, Half-sine, 0.5 ms Duration, 50g Pk, MIL-STD-810F, Method 516.5, Procedure I				
Vibration	16.3gRMS, MIL-STD-810F, Method 514.5, Procedure I, Category 24				
Altitude	80,000 f.t., MIL-STD-810F, Method 500.4, Procedure II				
Physical Dimensions					
Length (in./mm, ± 0.13 mm)	3.94/100				
Width (in./mm, ± 0.25 mm)	2.75/69.85				
Height (in./mm, max)	0.28/7				

¹As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3.0 Gb/s or SATA 1.5 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-I/O organization as of the date of this specification sheet. Visit www.sata-io.org for details.

²x = C (0°C to 70°C) or I (-40°C to 85°C)

³WD hard drive products manufactured and sold worldwide after June 1, 2006, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

⁴Measured with IOMeter 2008, 4 KB aligned transfers, queue depth 16.

⁵The term of the limited warranty may vary by region. Visit <http://support.wdc.com/warranty> for details.

⁶TBW specifications are in accordance with JESD47H.01 and JESD22-A117B. The values quoted are typical at 25°C.

Western Digital
3355 Michelson Drive, Suite 100
Irvine, California 92612
U.S.A.

For service and literature:

<http://support.wdc.com>
www.westerndigital.com

800.ASK.4WDC (800.275.4932) North America
800.832.4778 Spanish
+800.6008.6008 Asia Pacific
00800.27549338 Europe
(toll free where available)
+31.880062100 Europe/Middle East/Africa



Canada ICES-003 Class B / NMB-003 Classe B

Western Digital, WD, the WD logo, and SiliconDrive are registered trademarks in the U.S. and other countries; and LifeEST is a trademark of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.