

## HERMIT Series Industrial 2.5" IDE Flash disk



### Product features

- ❖ SLC - NAND type flash technology
- ❖ 2.5" IDE drive form-factor
- ❖ Extremely rugged metal casing to endure harsh environments
- ❖ Master / Slave selectable
- ❖ Compatible with ATA/ATAPI-6 standard
- ❖ Data transfer mode support PIO 0-6 and UDMA 0-5
- ❖ Performance up to 40MB/sec
- ❖ Capacity from 128MB up to 16GB

### Product specifications

<b>Compatibility</b>	❖ ATAPI-6 and True IDE mode
<b>Flash technology</b>	❖ SLC-NAND type flash based
<b>Form-factor</b>	❖ Rugged Metal 2.5" IDE hard disk drive
<b>Host Interface</b>	❖ Standard 44-pin IDE male connector

<b>Performance</b>	
Data transfer mode	❖ PIO-4 mode or UDMA-4 mode (def.)
Data transfer rate	❖ 66.6MB/sec (ATA-5 / UDMA-4)
	❖ 16.6MB/sec (ATA-3 / PIO-4)
Sequential read	❖ 40.0 MB/sec (Max. /with dual flash)
Sequential write	❖ 17.0 MB/sec (Max. /with dual flash)
Average access time	❖ 0.2ms (estimated)

<b>Environmental specification</b>	
Operating temp.	❖ STD. 0°C - 70°C / IND. -40°C - 85°C
Non-operating temp.	❖ STD. -20°C - 80°C / IND. -50°C - 95°C
Humidity	❖ 10% ~ 95% non-condensing
Vibration	❖ 15G compliance to MIL-STD-810F
Shock	❖ 1,500G compliance to MIL-STD-810F
Altitude	❖ 70,000 feet

<b>Power consumption</b>	
Power requirement	❖ +5V ± 10%
Reading mode	❖ 124.0 mA(Max.)
Writing mode	❖ 121.0 mA(Max.)
Sleeping mode	❖ 1.8 mA(Max.)

<b>Reliability</b>	
Wear-leveling	❖ Static wear-leveling algorithms
MTBF	❖ > 3,000,000 hours
ECC	❖ 4-bits per 512bytes block
Endurance	❖ > 2,000,000 cycles

<b>Physical specification</b>	
Weight (max.)	❖ 110g / 3.88 oz.
Dimension(W x L x H)	❖ 69.85 x 100.20 x 9.50 (mm)

<b>Conformal coating</b>	❖ Option for special request
<b>Warranty</b>	
Standard grade	❖ 3 years
Industrial grade	❖ 5 years

INDUSTRIAL  
CompactFlash Card

INDUSTRIAL  
PCMCIA ATA Card

INDUSTRIAL  
micro IDE Flash Disk

INDUSTRIAL  
micro SATA Flash Disk

INDUSTRIAL  
Solid State Disk

INDUSTRIAL  
4 Mini USB Flash Disk

INDUSTRIAL  
Card Reader

