

Product Specifications

3.5" 40-pin IDE to 1 PCMCIA PC card / 1 CF card Card-Drive

R325XX00I50XBH03R

Features :

- ❖ Standard 3.5" drive form-factor
- ❖ 1 front CompactFlash type II slot & 1 front PCMCIA type III slot
- ❖ ATA to standard 40-pin IDE interface
- ❖ 40-pin IDE connector and a 4-pin power connector
- ❖ Hot swappable & bootable
- ❖ Supports up to UDMA-4 mode
- ❖ RoHS compliant



Specifications :

| | |
|--------------------------------------|---|
| ❖ Form-factor | Standard 3.5" drive mounted in the front of PC casing |
| | Dimension 109.4mm (L) * 101.6mm (W) * 25.4mm (H) |
| | Weight G. W.: 230g (W/O Cable) |
| ❖ Host Interface | 40-pin IDE connector and a 4-pin power connector |
| ❖ Slot Capabilities | 1 front slot in CompactFlash type II |
| | 1 front slot in PCMCIA type III |
| ❖ Master/Slave Setting | By jumper |
| ❖ Supported Card Type | CompactFlash card type I/II and MicroDrive |
| | PCMCIA ATA flash card, ATA HDD, and CompactFlash card/ PC card adapter |
| ❖ Power Consumption | 5V / 75mA typ. |
| ❖ Environmental Specification | Operating Temperature 0°C ~ 70°C |
| | Non-operating Temperature -20°C ~ 80°C |
| | Relative Humidity Max 90% |
| ❖ Hot Swap Function | Yes and software supports DOS, Windows 98/ME/2000 /XP; no driver needed for Linux |
| ❖ Bootable Function | Yes and no driver needed |
| ❖ Data Access | PIO mode and DMA mode (up to UDMA-4 mode) |
| | (up to UDMA-4 mode) |
| ❖ Supported OS | Any OS workable per IDE interface |
| ❖ Warranty | 1 year |

Part Number List :

| | |
|-------------------|--|
| R325XX00I50XBH03R | 3.5" card drive with 1 CF card type II & PCMCIA type III to 40-pin IDE |
| | |

INDUSTRIAL CompactFlash Card

INDUSTRIAL PCMCIA ATA Card

INDUSTRIAL micro IDE Flash Disk

INDUSTRIAL micro SATA Flash Disk

INDUSTRIAL Solid State Disk

INDUSTRIAL Rugged Metal USB Flash Disk

INDUSTRIAL Adapter Card Reader